

SIDE POST UMBRELLAS

	Gulfstream 3.3 Metres	Gulfstream 3.5 Metres	Gulfstream 3.0 Metres	Gulfstream 3.0 x 4.0 Metres	Diablo 3.0 x 4.0 Metres	Jetstream 3.5 Metres	Jetstream 3.0 Metres
Shape	Octagonal	Octagonal	Square	Rectangle	Rectangle	Octagonal	Square
No of Arms	8	8	8	8	4 (& 2 Cross Bars)	8	8
Square Metres	8 Sq. Metres	9.2 Sq. Metres	9.0 Sq. Metres	12.0 Sq. Metres	12.0 Sq. Metres	9.2 Sq. Metres	9.0 Sq. Metres
Canopy Fabric	Olefin	Olefin	Olefin	Olefin	Olefin	O'bravia= 300 gm	O'bravia= 300 gm
*U.V. Rating % of U.V. Protection	*UPF 20 to 30 95% to 96%	*UPF 20 to 30 95% to 96%	*UPF 20 to 30 95% to 96%	*UPF 20 to 30 95% to 96%	*UPF 20 to 30 95% to 96%	*UPF 50 + 98%	*UPF 50 + 98%
Colours Available	Textured Beige Textured Licorice Solid Taupe	Textured Beige Textured Licorice Solid Taupe	Textured Beige Textured Licorice Solid Taupe	Textured Beige Textured Licorice Solid Taupe	Textured Beige Textured Licorice	Solid Rosewood Solid Platinum Solid Stone Solid Natural Sand	Solid Rosewood Solid Platinum Solid Stone Solid Natural Sand
Rotating System	Rotates thru 360 * with foot lock	Rotates thru 360 * with foot lock	Rotates thru 360 * with foot lock	Rotates thru 360 * with foot lock	N/A	Rotates thru 360 * with foot lock	Rotates thru 360 * with foot lock
Opening System	Wind-up crank lift opening/closing on handle	Wind-up crank lift opening/closing on handle	Wind-up crank lift opening/closing on handle	Wind-up crank lift opening/closing on handle	Retracting from awning housing, long handled Wind-up crank lift opening/closing	Wind-up crank lift opening/closing on mast	Wind-up crank lift opening/closing on mast
Tilting System	Pistol grip, press button tilt lock, 6 position tilt to 25*	Pistol grip, press button tilt lock, 6 position tilt to 25*	Pistol grip, press button tilt lock, 6 position tilt to 25*	Pistol grip, press button tilt lock, 6 position tilt to 25*	Variable double sided awning angles	Finger light 'easy track' variable angle tilt to 25* with locking wheel	Finger light 'easy track' variable angle tilt to 25* with locking wheel
Mast Colour Material	Metalic Graphite powder coat finish on Extruded & cast aluminium	Metalic Graphite powder coat finish on Extruded & cast aluminium	Metalic Graphite powder coat finish on Extruded & cast aluminium	Metalic Graphite powder coat finish on Extruded & cast aluminium	Metalic Graphite powder coat finish on All steel construction	Metalic Graphite powder coat finish on Extruded & cast aluminium	Metalic Graphite powder coat finish on Extruded & cast aluminium
Measurements cm A (Canopy Width) B (Mast Height) C (Level canopy height) D (Total depth incl mast)	330 260 210 360	350 260 230 380	290 270 220 330	300 x 400 290 240 330	380 x 320 245 Variable 160 x 240 400	350 250 210 370	300 250 210 320
Arm Size Mast Size	14 x 24 mm 77 x 53 mm - Oval	17 x 25 mm 95 x 65 mm - Oval	14 x 24 mm 77 x 53 mm - Oval	17 x 25 mm 95 x 65 mm - Oval	18 x 36 mm 57 mm Diam - Rnd x 2	14 x 28 mm 80 x 60 mm - Oval	14 x 28 mm 80 x 60 mm - Oval
Installation Options	1 / Ground Mount Plate (Optional purchase) For securing onto concrete base/foundation 2 / 'X' shaped Steel concrete ballast frame base (Supplied)	1 / Ground Mount Plate (Optional purchase) For securing onto concrete base/foundation 2 / 'X' shaped Steel concrete ballast frame base (Supplied)	1 / Ground Mount Plate (Optional purchase) For securing onto concrete base/foundation 2 / 'X' shaped Steel concrete ballast frame base (Supplied)	1 / Ground Mount Plate (Optional purchase) For securing onto concrete base/foundation 2 / 'X' shaped Steel concrete ballast frame base (Supplied)	2 x 'X' shaped Steel concrete ballast frame bases (Supplied) (Can also bolt down these bases for securing onto concrete base/foundation)	1 / Ground Mount Plate (Optional purchase) For securing onto concrete base/foundation 2 / 'X' shaped Steel concrete ballast frame base (Supplied) 3/ Extra large wheeled resin base (Optional)	1 / Ground Mount Plate (Optional purchase) For securing onto concrete base/foundation 2 / 'X' shaped Steel concrete ballast frame base (Supplied) 3/ Extra large wheeled resin base (Optional)
*Installation Weight	*100 kg (Recommended)	*120 kg (Recommended)	*120 kg (Recommended)	*160 kg (Recommended)	*200 kg (Recommended)	*120 kg (Recommended)	*120 kg (Recommended)
No of Ballast Pavers -18-20 kg each	5	6	6	8	10 (5 on each base)	6	6
Warranty - Frame	1 Year	1 Year	1 Year	1 Year	1 Year	2 Year	2 Year
- Canopy	2 Years	2 Years	2 Years	2 Years	2 Years	4 Years	4 Years
Extra Features	Protective cover Included	Protective cover Included	Protective cover Included	Protective cover Included	Canopy / Awning retracts into and out of roller housing	1/ Protective cover included 2/ Retractable L.E.D. Light bracket on hub 3/ Spring adjusting canopy tentioning finger ends	1/ Protective cover included 2/ Retractable L.E.D. Light bracket on hub 3/ Spring adjusting canopy tentioning finger ends
Ctn Weight- kgs	29.5	32.5	29.5	36.3	58	31	32